

# Asphalt Primer

# PG-0016

## Description

Durapax Asphalt Primer is a select blend of oxidized asphalt and refined solvents, designed to penetrate porous surfaces and bind, chalky dusty surfaces.

Durapax Asphalt Primer enhances the adhesion of BUR, modified bitumen roofing systems, and protective coatings.

It can also be used as a wood fence paint or rust inhibitor over metal surfaces.

## Features

- Saturates and binds exposed, dry or dusty roofing felts and scrims.
- Can be applied by brush, roller or airless spray equipment.
- Meets current VOC requirements, except for California.
- Non-Asbestos
- ASTM D41

## Uses

- Creates a bondable surface over existing built up roofs.
- Thoroughly penetrates and binds concrete and masonry surfaces, prior to application of subsequent surfacing.
- Rust proofs and promotes adhesion to metal surfaces.

## Application

- Ready to apply. Do not heat. Do not thin.

## Surface Preparation

- All surfaces must be clean, dry, free of heavy dirt, dust, debris, oils, loose gravel, un-adhered coatings, loose, scaling rust, deteriorated membranes, and other contaminants that may result in a surface that is not sound.
- Surface must be free of frost, snow and ice.
- All necessary repairs must be completed before application to ensure optimum performance.
- Fasteners must be repaired and/or replaced as needed.

## Application Directions

- Apply to the prepared surface at the rate of 1/2 to 3/4 gallons per square.
- Application of two coats, applied perpendicular to one another and at one-half the total recommended coverage rate, will ensure optimum performance of the primer and subsequent surfacing.

## Application Precautions

- DO NOT use on 100% rubber or plastic substrate.
- DO NOT use on products containing coal tar.
- DO NOT apply to damp or wet surfaces.
- DO NOT use where this product may come in contact with potable water.
- DO NOT THIN.
- EXTERIOR USE ONLY.

## Clean Up

- Immediately rinse/flush equipment and tools with mineral spirits after use, exercising all flammable liquid precautions.
- Use waterless hand cleaner on skin.

## Typical Properties

Property	Test Method	Result
Wt/gal, lbs.	D6511	7.2-7.6
Solids, % by wt	D6511	52-57
% by vol		50-53
Viscosity, seconds	Saybolt Furol	25-75
pH		N/A
Flash Point, °F	PMCC	105 min.
Color, uncured & cured	Visual	Black
Drying time, Touch	70 °F/50% R.H.	2 hours
Shelf life	70 °F/50% R.H.	1 year
VOC	EPA Method 24A	450 gm/liter max.

## Packaging

- 5-gallon pails (40 lbs.).

## Specification Compliances

- ASTM D41.

## Safety and Environmental Precautions

- Consult MSDS for detailed handling and disposal.