

## Base Sheets

### Description

Durapax Base Sheets are designed for use with Durapax coal tar roofing systems. Durapax offers both organic and glass fiber base sheets.

### Organic Base Sheet BS-1001

Durapax Organic Base Sheet is manufactured using an organic base felt saturated and heavily coated on both sides with a coating grade asphalt.

Meets ASTM D-2626

Roll Width: 36 inches

Average Coverage/Roll: 200 sq. ft.

Approx. Weight/Roll: 86 lbs.

### Glass Fiber Base Sheet BS-2001

Durapax Glass Fiber Base Sheet is manufactured from high quality glass fiber mat, coated with asphalt and lightly dusted with a fine mineral surfacing.

Meets ASTM D-4601 Type II

Roll Width 36 inches

Actual Coverage/Roll 300 sq. ft.

Approx. Weight /Roll 75 lbs.

### Typical Properties

Base Sheet	Glass Fiber	Organic
Roll Length	108 ft.	72 ft.
Roll Width	36 inches	36 inches
Roll Area	324 sq. ft.	216 sq. ft.
Coverage per roll	300 sq. ft. (3 sq. roll)	200 sq. ft. (2 sq. roll)

### Storage/Handling

As with most building components, base sheets are susceptible to the effects of moisture prior to being installed. Care must be taken to keep the base sheets dry and clean.

### Product Safety Information

#### Organic Base Sheets

Durapax Organic Base Sheets contain asphalt which requires caution to be used in a safe manner. Proper dress and normal safety procedures recommended for installing a built-up roof will, for the most part, satisfy this product's requirements. Persons with sensitive skin may require additional protection

For specific information contact your Durapax representative for an up-to-date Material Safety Data Sheet on this product. Or contact Durapax Commercial Roofing Systems direct at 610-579-9075. In case of emergency, information can be obtained by calling the Durapax Chemtrec 24 hour emergency number, 800-424-9300.

#### Glass Fiber Base Sheets

Durapax Glass Fiber Base Sheets contain glass fibers and asphalt which require caution to be used in a safe manner. Proper dress and normal safety procedures recommended for installing a built-up roof will, for the most part, satisfy this product's requirements. Persons with sensitive skin may require additional protection.

For specific information contact your Durapax representative for an up-to-date Material Safety Data Sheet on this product. Or contact Durapax Commercial Roofing Systems direct at 610-579-9075. In case of emergency, information can be obtained by calling the Durapax Chemtrec 24 hour emergency number, 800-424-9300.

### Note

All statements, information and data given herein are believed to be accurate and reliable but are presented without guaranty, warranty or responsibility of any kind, expressed or implied, except as may be otherwise specifically indicated.

Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated or that other measures may not be required.