



METAL SET IN ASPHALT MASTIC-PRIME FLANGE BEFORE STRIPPING

JOINT COVER 4" TO 6" WIDE SET IN ASPHALT MASTIC

NAILS APPROX. 3" O.C. STAGGERED

2 PLY STRIPPING SET IN COAL TAR PITCH

ASPHALT MASTIC

METAL PITCH DAM (1" X 3") SET IN ASPHALT MASTIC AND NAILED TO WOOD AND STRIPPED WITH 2 PLYS OF ORGANIC FELT SET IN ASPHALT MASTIC OR STEEP ASPHALT. MIN. 2" END LAPS SET IN ASPHALT MASTIC.

COAL TAR PITCH BUR PLYS

DOUBLE LAYER INSULATION TOP LAYER SET IN STEEP ASPHALT. JOINTS BETWEEN LAYERS TO BE STAGGERED THE MAXIMUM DISTANCE POSSIBLE. JOINTS SHOULD NOT BE CLOSER THAN 12 INCHES.

DECK

TURN ONE PLY DOWN BELOW WOOD NAILER

CONTINUOUS CLEAT

DURAPAXTM
COAL TAR
 COMMERCIAL ROOFING SYSTEMS

METAL PITCH DAM

DATE: 1-1-06

SCALE: NONE

DRAWING NO.: B62ISO